

Also known as:



ROBOTICS "CRACK" !!

VERY ADDICTIVE !





Version 02: Carriages with threaded boss

2 1 :	Data:	
5	Part No. carriage	
	Part No. rail	
	Rall weight	3.
	Carriage weight	
	Max. rail length	-
	Standard oore pattern	Sy
	Preload available	
	for reduced clearance	

Jala.	
Part No. carriage	NW-02-27(P)
Part No. rail	NS-01-27
Rail weight	3.01 oz. (290 g/m)
Carriage weight	.44 oz. (12.5 g)
Max. rail length	140 in (3560 mm)
Standard oore pattern	symmetrical (C5 = C6)
Preload available	Yes
or reduced clearance	.22 lbs (1N)

18"-



igubal ® Flange **Mount Spherical** Bearing x6




Dryline[®] Low Profile Linear Guide system x2


Dryline® S ¹/₄" Diam. Hard Anodized Aluminum Shaft, 18" Length x2



igubal ® 1/4" Rod End Bearing x6





1/4" thick polypropylene sheet 12" x 24"




1/8" thick PVC sheet 12" x 24"














2.5" x 5/8", Iron ZN,Corner Angle Bracket x4

2" x 3/8", Iron ZN,Flat Angle Bracket x4



2.5"H x 1.69"W x 0.083" narrow hinge w/removable pin x2



1.5"H x 1.41"W x 0.047" narrow hinge w/nonremovable pin x2

Extension Spring for Heavy Doors



³/₄" metal pipe hanger tape, 24 Gauge, 10 ft.



6" x 6" Steel Turntable, 500 Pound Capacity






18 ga stranded copper wire, red insulation, single cond.

18 ga stranded copper wire, black insulation, single cond.





CAT-3 24guage, 4 twisted pairs



snap-plug terminals (bullet connectors), insulated, male x16

snap-plug terminals (socket for bullet connectors), insulated, female x16









Rotary potentiometer 10kohm, 6mm shaft x2

sub-mini snap acting switch, SPDT, 0.1 amp (min) x4





4" long x 0.1" wide nylon cable tie x20



nylon cable tie x10



vinyl electrical tape, 3/4" Wide, 60 ft



friction tape, 3/4" Wide, 60 ft



all purpose duct tape, 2" Wide, 60 yd



Painter's tape, 1" Wide, 60 yd




carpenters wood glue, 4 oz



5 minute epoxy 1 oz

<u>Tapes & Adhesives</u>





readed Fasteners

Hex / Slotted Drive NOTE: Use of a *slotted screwdriver* is *NOT RECOMMENDED!!* The slot is shallow and strips out easily! Use a Nut Driver on the hexagonal head!



<u>**Threaded Fasteners**</u>



1/4-20 Threaded Rod, 3' long



1/4-20 Hex Nut, steel x25



1/4 SAE flat washer, steel x25



1/4 med. split lock washer, steel x25



1/4-28 x 1" screw, nylon x6



10-32 x 1-1/2" machine screws, steel, round head, phillips x25



#10-32 machine screw nut, steel x25



#10 flat washer, steel x25



#8-32 x 1-1/4" machine screws, steel, pan head, phillips x100



#8-32 machine screw nuts. x100 steel



#8 med. split lock washer, steel x25



10-32 x 3/4" screw, socket head x6

eaded Fasteners



#4-40 x 1" machine screws, steel, **round** head, phillips x25



#4-40 machine screw nut, steel x25



#2-56 x 1" machine screws, **pan** head, phillips, stainless x10




#2-56 machine screw nuts, 3/16 x1/16, steel x10



#2 flat washer, steel x10


<u>Threaded Fasteners</u>



wood screw eyebolts, 0.192 wire dia x .97 shank x .75 thread x .27 id, steel x10




#8 X 1" sheet metal screw, steel, hex head x100



#4 X 3/4" wood

screw, steel, slotted drive, round head x25

<u>Threaded Fasteners</u>




3/4" nylon sticky back hook and loop fastener 5 ft



1/4" polypropylene covered shock cord (color optional) 4 ft #18 twisted nylonseine twine,225-250 ft long





3/8" thick, 1" wide, adhesive backed, gum rubber strip 2 ft

<u>Miscellaneous</u>



bicycle inner tube (26" X 1.5" - 2.0")

> 60x65" universal brake cable with housing (white or black)



#10 Rubber Band (1/16" wide x 1-1/4" long) x25 #32 Rubber Band (1/8" wide x 3" long) x25





1 1/4" long paper clips, 0.033 dia wire (No. 1 Regular) x100

VEX motor mount kit (4 mounts+ screws)

<u>Miscellaneous</u>